



QUICK-FIT INSTALLATION GUIDE **Air Lumbar Support System**

ALSCA



ALSSS



PART NUMBER

ALSCA (Canvas) | ALSSS (Sheepskin)



CONGRATULATIONS ON YOUR PURCHASE OF AN MSA 4X4 QUALITY Air Lumbar Support System

FITTING INSTRUCTIONS:

1. Remove the head rest from the seat
2. Place the head rest posts through the two holes in the top of the binding on the lumbar support. If post holes do not align, refer to (6).
3. Re-install the head rest onto the seat
4. Insert the supplied air bladder through the base of the lumbar support. Place the bladder in your desired position by affixing the bladder to the relevant internal Velcro strip
5. Keeping the air hose clear of all tie straps, join the side straps around seat pivot adjuster from front to rear
6. Feed the vertical straps between the upper and lower seat back and fasten length-ways. Tension all straps firmly
7. Pump rubber valve to inflate bladder to desired pressure. Push button on side of valve to deflate

PLEASE NOTE: On 120 / 150 series Toyota Prado there is a black flap joining the upper and lower seats. This is held in place with two elastics. These will need to be released and folded up and out of the way to allow straps to feed through between the upper and lower seat.

**Designed and Distributed by MSA
4X4 Accessories Pty Ltd**

43 Harrington Street
Arundel, QLD 4214 Australia
Phone: (07) 5594 6664

www.msa4x4.com.au

ABN: 50 150 429 566



Please refer to our website for
lifetime guarantee full terms
and conditions.